

SERIE 114

108BISB

AVO - Wheel with mechanical cast iron and steel castor for industry,
diameter 100mm ean 23215

Material: Mechanical Cast
iron

Core: Cast
Iron

Application field:
Industry

Description:

Cast iron wheel, high temperatures resistant with low rolling resistance with pearlitic or laminar structure in accordance with ISO 185. Hub on plain bore.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem and rear brake. Black epoxy paint.

Product line: Cast Iron, High temperature

EAN13:8018793232159 **EAN5:**23215 **Article code:**04108BF1000GM



Features

Minimum temperature: -40

Maximum temperature: 500

Dynamic load capacity: 250 DaN

- Asphalt
- Concrete

Rotation: Plain bore

Hardness scale: HB

Hardness: 200

Flooring

Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	250
Colour	Grey
Material	Mechanical Cast iron
Box pieces	/
Hardness scale	HB
Hardness	200

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	36
Ground clearance (mm)	150
Castor hole (mm)	/
Static load capacity (DaN)	320
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	20X50
Stem type	Stem(on request threaded stem) Plain axle
Finishing	Black painted