Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114A

# 106B

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 125mm ean 05515

Material: Mechanical Cast Core: Cast Application field:

#### Description:

Cast iron wheel, resistant to high temperatures with low rolling resistance. Hub on shielded ball bearings. Special ball bearings for high or low temperatures are available on request.

#### **Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem. Assembled with self-locking nut.

Product line: High temperature, Cast Iron

**EAN13**:8018793055154 **EAN5**:05515 **Article code**:04106B01250GP



Features Flooring

Minimum temperature: -20 Maximum temperature: 120 Dynamic load capacity: 400 DaN

Rotation: Ball bearing Hardness scale: HB Hardness: 200

AsphaltConcrete

### Wheel data

Diameter (mm)	125
Band width (mm)	32
Hub width (mm)	32
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	400
Colour	Grey
Material	Mechanical Cast iron
Box pieces	1
Hardness scale	НВ
Hardness	200

## Support data

Plate size (mm)	1
Plate hole spacing (mm)	/
Plate hole size (mm)	1
Offset (mm)	45
Ground clearance (mm)	161
Castor hole (mm)	1
Static load capacity (DaN)	500
Structure	Swivel
Version	Axle
Brake	1
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized