Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114

108

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 125mm ean 14622

Material: Mechanical Cast iron Core: Cast Iron Scope: Industry

Description

Cast iron wheel, high temperatures resistant with low rolling resistance with pearlitic or laminar structure in accordance with ISO 185. Hub on plain bore.

**Extra Heavy-Duty Castors:** 

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate. Black epoxy paint.

Product line: High temperature, Cast Iron



Features Flooring

Minimum temperature: -40 Maximum temperature: 500 Dynamic load capacity: 250 DaN

Rotation: Plain bore Hardness scale: HB Hardness: 200

AsphaltConcrete

## Wheel data

Diameter (mm)	125
Band width (mm)	35
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	I
Dynamic load capacity (DaN)	250
Colour	Grey
Material	Mechanical Cast iron
Box pieces	1
Hardness scale	НВ
Hardness	200

## Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13
Offset (mm)	45
Ground clearance (mm)	175
Castor hole (mm)	1
Static load capacity (DaN)	320
Structure	Swivel
Version	Plate
Brake	1
Plain axle	1
Stem type	1
Finishing	Black painted