Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114

105A

AVO - Wheel made of mechanical cast iron with steel castor for industry, diameter 125mm ean 15676

Material: Mechanical Cast iron Core: Cast Iron Scope: Industry

Description

Cast iron wheel, high temperatures resistant with low rolling resistance with pearlitic or laminar structure in accordance with ISO 185. Hub on plain bore.

Medium duty castors:

 $\label{thm:made} \mbox{Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking}$ 

nut.

Product line: High temperature, Cast Iron

**EAN13**:8018793156769 **EAN5**:15676 **Article code**:04105SA1250GM



Features Flooring

Minimum temperature: -40 Maximum temperature: 500 Dynamic load capacity: 130 DaN

Rotation: Plain bore Hardness scale: HB Hardness: 200

AsphaltConcrete

## Wheel data

Diameter (mm)	125
Band width (mm)	35
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	1
Dynamic load capacity (DaN)	130
Colour	Grey
Material	Mechanical Cast iron
Box pieces	1
Hardness scale	НВ
Hardness	200

## Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	1
Ground clearance (mm)	155
Castor hole (mm)	/
Static load capacity (DaN)	170
Structure	Fixed
Version	1
Brake	1
Plain axle	1
Stem type	1
Finishing	Galvanized