Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114A

# **106BIS**

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 125mm ean 18552

Material: Mechanical Cast Core: Cast Application field:

#### Description:

Cast iron wheel, resistant to high temperatures with low rolling resistance. Hub on shielded ball bearings. Special ball bearings for high or low temperatures are available on request.

#### **Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate and rear brake. Assembled with self-locking nut.

Product line: High temperature, Cast Iron

**EAN13**:8018793185523 **EAN5**:18552 **Article code**:041060F1250GP



Features Flooring

Minimum temperature: -20 Maximum temperature: 120 Dynamic load capacity: 400 DaN

Rotation: Ball bearing Hardness scale: HB Hardness: 200

AsphaltConcrete

### Wheel data

Diameter (mm)	125
Band width (mm)	32
Hub width (mm)	32
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	400
Colour	Grey
Material	Mechanical Cast iron
Box pieces	1
Hardness scale	НВ
Hardness	200

## Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	46
Ground clearance (mm)	166
Castor hole (mm)	/
Static load capacity (DaN)	500
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	1
Stem type	1
Finishing	Galvanized