Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114

105ANT

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 125mm ean 20584

Material: Mechanical Cast iron

Core: Cast Iron Application field:

Industry

Description:

Cast iron wheel, high temperatures resistant with low rolling resistance with pearlitic or laminar structure in accordance with ISO 185. Hub on plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls

Product line: High temperature, Cast Iron

EAN13:8018793205849

EAN5:20584

Article code:041050A1250GM



Features Flooring

Minimum temperature: -40

Maximum temperature: 500

Hardness scale: HB

Dynamic load capacity: 170 DaN

Hardness: 200

AsphaltConcrete

Wheel data

Rotation: Plain bore

Diameter (mm)	125
Band width (mm)	35
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	1
Dynamic load capacity (DaN)	170
Colour	Grey
Material	Mechanical Cast iron
Box pieces	1
Hardness scale	НВ
Hardness	200

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	42
Ground clearance (mm)	155
Castor hole (mm)	1
Static load capacity (DaN)	220
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	1
Stem type	1
Finishing	Galvanized