Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114

107BIS

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 125mm ean 20630

Material: Mechanical Cast iron Core: Cast Iron Scope: Industry

Description:

Cast iron wheel, high temperatures resistant with low rolling resistance with pearlitic or laminar structure in accordance with ISO 185. Hub on plain bore.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate and rear brake. Assembled with self-locking nut.

Product line: High temperature, Cast Iron

EAN13:8018793206303 **EAN5**:20630 **Article code**:041070F1250GM



Features Flooring

Minimum temperature: -40 Maximum temperature: 500 Dynamic load capacity: 250 DaN

Rotation: Plain bore Hardness scale: HB Hardness: 200

AsphaltConcrete

Wheel data

| Diameter (mm) | 125 |
|-----------------------------|----------------------|
| Band width (mm) | 35 |
| Hub width (mm) | 50 |
| Hub version | Plain bore |
| Wheel hole (mm) | 15 |
| Bearing seat (mm) | 1 |
| Dynamic load capacity (DaN) | 250 |
| Colour | Grey |
| Material | Mechanical Cast iron |
| Box pieces | 1 |
| Hardness scale | НВ |
| Hardness | 200 |

Support data

| Plate size (mm) | 135X110 |
|----------------------------|------------------|
| Plate hole spacing (mm) | 105X080 |
| Plate hole size (mm) | 13X16 |
| Offset (mm) | 45 |
| Ground clearance (mm) | 166 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 320 |
| Structure | Swivel |
| Version | Plate with brake |
| Brake | Rear |
| Plain axle | 1 |
| Stem type | 1 |
| Finishing | Galvanized |