Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia





SERIE 114

105ANTF

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 125mm ean 26903

Material: Mechanical Cast iron Core: Cast Iron Scope: Industry

Description

Cast iron wheel, high temperatures resistant with low rolling resistance with pearlitic or laminar structure in accordance with ISO 185. Hub on plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole and front brake. Assembled with self-locking nut.

Product line: High temperature, Cast Iron

EAN13:8018793269032 **EAN5**:26903 **Article code**:04105FA1250GM



Features Flooring

Minimum temperature: -40 Maximum temperature: 500 Dynamic load capacity: 170 DaN

Rotation: Plain bore Hardness scale: HB Hardness: 200

AsphaltConcrete

Concrete

Wheel data

Diameter (mm)	125
Band width (mm)	35
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	1
Dynamic load capacity (DaN)	170
Colour	Grey
Material	Mechanical Cast iron
Box pieces	1
Hardness scale	НВ
Hardness	200

Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	42
Ground clearance (mm)	155
Castor hole (mm)	12
Static load capacity (DaN)	220
Structure	Swivel
Version	Bolt hole with brake
Brake	Front
Plain axle	1
Stem type	1
Finishing	Galvanized