Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114

# **105ANTF**

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 125mm ean 26903

**Material:** Mechanical Cast iron

Core: Cast Iron Application field:

Industry

#### Description:

Cast iron wheel, high temperatures resistant with low rolling resistance with pearlitic or laminar structure in accordance with ISO 185. Hub on plain bore.

#### Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole and front brake. Assembled with self-locking nut.

Product line: High temperature, Cast Iron

**EAN13**:8018793269032 **EAN5**:26903

Article code:04105FA1250GM



Features Flooring

Minimum temperature: -40

Maximum temperature: 500

Dynamic load capacity: 170 DaN

AsphaltConcrete

Rotation: Plain bore

Hardness scale: HB

Hardness: 200

### Wheel data

| Diameter (mm)               | 125                  |
|-----------------------------|----------------------|
| Band width (mm)             | 35                   |
| Hub width (mm)              | 50                   |
| Hub version                 | Plain bore           |
| Wheel hole (mm)             | 15                   |
| Bearing seat (mm)           | 1                    |
| Dynamic load capacity (DaN) | 170                  |
| Colour                      | Grey                 |
| Material                    | Mechanical Cast iron |
| Box pieces                  | 1                    |
| Hardness scale              | НВ                   |
| Hardness                    | 200                  |

## Support data

| Plate size (mm)            | 1                    |
|----------------------------|----------------------|
| Plate hole spacing (mm)    | 1                    |
| Plate hole size (mm)       | 1                    |
| Offset (mm)                | 42                   |
| Ground clearance (mm)      | 155                  |
| Castor hole (mm)           | 12                   |
| Static load capacity (DaN) | 220                  |
| Structure                  | Swivel               |
| Version                    | Bolt hole with brake |
| Brake                      | Front                |
| Plain axle                 | 1                    |
| Stem type                  | 1                    |
| Finishing                  | Galvanized           |