

SERIE 114A

109BISB

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 125mm ean 27738

Material: Mechanical Cast iron

Core: Cast Iron

Application field:
Industry

Description:

Cast iron wheel, resistant to high temperatures with low rolling resistance. Hub on shielded ball bearings. Special ball bearings for high or low temperatures are available on request.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem and rear brake. Black epoxy paint.

Product line: High temperature, Cast Iron

EAN13:8018793277389 **EAN5:**27738 **Article code:**04109BF1250GP



Features

Minimum temperature: -20

Maximum temperature: 120

Dynamic load capacity: 500 DaN

- Asphalt
- Concrete

Rotation: Ball bearing

Hardness scale: HB

Hardness: 200

Flooring

Wheel data

Diameter (mm)	125
Band width (mm)	32
Hub width (mm)	32
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	500
Colour	Grey
Material	Mechanical Cast iron
Box pieces	/
Hardness scale	HB
Hardness	200

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	45
Ground clearance (mm)	175
Castor hole (mm)	/
Static load capacity (DaN)	630
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Black painted