Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



SERIE 114A

## **106BISB**

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 125mm ean 27921

Material: Mechanical Cast iron Core: Cast Iron Scope: Industry

#### Description:

Cast iron wheel, resistant to high temperatures with low rolling resistance. Hub on shielded ball bearings. Special ball bearings for high or low temperatures are available on request.

**Heavy-Duty Castors:** 

Product line: High temperature, Cast Iron

**EAN13**:8018793279215 **EAN5**:27921 **Article code**:04106BA1250GP



Features Flooring

Minimum temperature: -20 Maximum temperature: 120 Dynamic load capacity: 400 DaN

Rotation: Ball bearing Hardness scale: HB Hardness: 200

# AsphaltConcrete

#### Wheel data

Diameter (mm)	125
Band width (mm)	32
Hub width (mm)	32
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	400
Colour	Grey
Material	Mechanical Cast iron
Box pieces	1
Hardness scale	НВ
Hardness	200

### Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	45
Ground clearance (mm)	161
Castor hole (mm)	1
Static load capacity (DaN)	500
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized