Via XX Settembre, 107 28883 Gravellona Toce (VB) - Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 125mm ean 27929

Material: Mechanical Cast Core: Cast iron

Iron

Application field:

Industry

Description:

Cast iron wheel, high temperatures resistant with low rolling resistance with pearlitic or laminar structure in accordance with ISO 185. Hub on plain bore.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem and rear brake. Black epoxy paint.

Product line: High temperature, Cast Iron

EAN13:8018793279291 EAN5:27929 Article code:04108BF1250GM



Flooring Features

Minimum temperature: -40 Dynamic load capacity: 250 DaN Maximum temperature: 500

Rotation: Plain bore Hardness scale: HB Hardness: 200 Asphalt Concrete

Wheel data

Diameter (mm)	125
Band width (mm)	35
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	1
Dynamic load capacity (DaN)	250
Colour	Grey
Material	Mechanical Cast iron
Box pieces	1
Hardness scale	НВ
Hardness	200

Support data

Plate size (mm)	1
Plate hole spacing (mm)	/
Plate hole size (mm)	1
Offset (mm)	45
Ground clearance (mm)	175
Castor hole (mm)	1
Static load capacity (DaN)	320
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Black painted