Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



SERIE 114

105

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 140mm ean 05499

**Material:** Mechanical Cast iron

Core: Cast Iron Application field:

Industry

Description:

Cast iron wheel, high temperatures resistant with low rolling resistance with pearlitic or laminar structure in accordance with ISO 185. Hub on plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate. Assembled with self-locking nut and dust cover ring on the balls.

Product line: High temperature, Cast Iron

EAN13:8018793054997

EAN5:05499

Article code:04105001400GM



Features Flooring

Minimum temperature: -40

Maximum temperature: 500

Dynamic load capacity: 200 DaN

AsphaltConcrete

Rotation: Plain bore

Hardness scale: HB

Hardness: 200

## Wheel data

Diameter (mm)	140
Band width (mm)	35
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	1
Dynamic load capacity (DaN)	200
Colour	Grey
Material	Mechanical Cast iron
Box pieces	1
Hardness scale	НВ
Hardness	200

## Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	45
Ground clearance (mm)	176
Castor hole (mm)	/
Static load capacity (DaN)	250
Structure	Swivel
Version	Plate
Brake	1
Plain axle	1
Stem type	1
Finishing	Galvanized