

SERIE 114

105F

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 140mm ean 15159

Material: Mechanical Cast iron

Core: Cast Iron

Application field: Industry

Description:

Cast iron wheel, high temperatures resistant with low rolling resistance with pearlitic or laminar structure in accordance with ISO 185. Hub on plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole. Assembled with self-locking nut.

Product line: High temperature, Cast Iron

EAN13: 8018793151597

EAN5: 15159

Article code: 04105F01400GM



Features

Minimum temperature: -40

Maximum temperature: 500

Dynamic load capacity: 200 DaN

Rotation: Plain bore

Hardness scale: HB

Hardness: 200

Flooring

- Asphalt
- Concrete

Wheel data

Diameter (mm)	140
Band width (mm)	35
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	200
Colour	Grey
Material	Mechanical Cast iron
Box pieces	/
Hardness scale	HB
Hardness	200

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	45
Ground clearance (mm)	173
Castor hole (mm)	12
Static load capacity (DaN)	250
Structure	Swivel
Version	Bolt hole
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized