Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114A

106A

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 150mm ean 05507

Material: Mechanical Cast iron Core: Cast Iron Scope: Industry

Description:

Cast iron wheel, resistant to high temperatures with low rolling resistance. Hub on shielded ball bearings. Special ball bearings for high or low temperatures are available on request.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking put

Product line: High temperature, Cast Iron

EAN13:8018793055079 **EAN5**:05507 **Article code**:04106A01500GP



Features Flooring

Minimum temperature: -20 Maximum temperature: 120 Dynamic load capacity: 500 DaN

Rotation: Ball bearing Hardness scale: HB Hardness: 200

AsphaltConcrete

Wheel data

Diameter (mm)	150
Diameter (mm)	100
Band width (mm)	38
Hub width (mm)	38
Hub version	Ball bearing
Wheel hole (mm)	17
Bearing seat (mm)	40X12
Dynamic load capacity (DaN)	500
Colour	Grey
Material	Mechanical Cast iron
Box pieces	1
Hardness scale	НВ
Hardness	200

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	1
Ground clearance (mm)	189
Castor hole (mm)	1
Static load capacity (DaN)	630
Structure	Fixed
Version	1
Brake	1
Plain axle	1
Stem type	1
Finishing	Galvanized