

SERIE 114A

106

AVO - Wheel with mechanical cast iron and steel castor for industry,
diameter 150mm ean 05524

Material: Mechanical Cast
iron

Core: Cast
Iron

Application field:
Industry

Description:

Cast iron wheel, resistant to high temperatures with low rolling resistance. Hub on shielded ball bearings. Special ball bearings for high or low temperatures are available on request.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate. Assembled with self-locking nut.

Product line: High temperature, Cast Iron

EAN13:8018793055246

EAN5:05524

Article code:04106001500GP



Features

Minimum temperature: -20

Maximum temperature: 120

Dynamic load capacity: 500 DaN

Rotation: Ball bearing

Hardness scale: HB

Hardness: 200

Flooring

- Asphalt
- Concrete

Wheel data

Diameter (mm)	150
Band width (mm)	38
Hub width (mm)	38
Hub version	Ball bearing
Wheel hole (mm)	17
Bearing seat (mm)	40X12
Dynamic load capacity (DaN)	500
Colour	Grey
Material	Mechanical Cast iron
Box pieces	/
Hardness scale	HB
Hardness	200

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	50
Ground clearance (mm)	189
Castor hole (mm)	/
Static load capacity (DaN)	630
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized