Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114A

109A

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 150mm ean 14635

Material: Mechanical Cast iron Core: Cast Iron Scope: Industry

Description:

Cast iron wheel, resistant to high temperatures with low rolling resistance. Hub on shielded ball bearings. Special ball bearings for high or low temperatures are available on request.

**Extra Heavy-Duty Castors:** 

Made of in pressed and welded high thickness steel, fixed. Black epoxy paint.

Product line: High temperature, Cast Iron



Features Flooring

Minimum temperature: -20 Maximum temperature: 120 Dynamic load capacity: 750 DaN

Rotation: Ball bearing Hardness scale: HB Hardness: 200

AsphaltConcrete

## Wheel data

Diameter (mm)	150
Band width (mm)	38
Hub width (mm)	38
Hub version	Ball bearing
Wheel hole (mm)	17
Bearing seat (mm)	40X12
Dynamic load capacity (DaN)	750
Colour	Grey
Material	Mechanical Cast iron
Box pieces	1
Hardness scale	НВ
Hardness	200

## Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13
Offset (mm)	1
Ground clearance (mm)	205
Castor hole (mm)	/
Static load capacity (DaN)	940
Structure	Fixed
Version	1
Brake	1
Plain axle	1
Stem type	1
Finishing	Black painted