Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114A

# 109B

 $\mbox{AVO}$  - Wheel with mechanical cast iron and steel castor for industry, diameter 150mm ean 14640

**Material:** Mechanical Cast iron

Core: Cast Iron

Application field:

Industry

#### Description:

Cast iron wheel, resistant to high temperatures with low rolling resistance. Hub on shielded ball bearings. Special ball bearings for high or low temperatures are available on request.

#### **Extra Heavy-Duty Castors:**

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem. Black epoxy paint.

Product line: High temperature, Cast Iron

EAN13:8018793146401

EAN5:14640

Article code:04109B01500GP



Features Flooring

Minimum temperature: -20

Maximum temperature: 120

Dynamic load capacity: 750 DaN

AsphaltConcrete

Rotation: Ball bearing

Hardness scale: HB

Hardness: 200

### Wheel data

Diameter (mm)	150
Band width (mm)	38
Hub width (mm)	38
Hub version	Ball bearing
Wheel hole (mm)	17
Bearing seat (mm)	40X12
Dynamic load capacity (DaN)	750
Colour	Grey
Material	Mechanical Cast iron
Box pieces	1
Hardness scale	НВ
Hardness	200

## Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	50
Ground clearance (mm)	205
Castor hole (mm)	/
Static load capacity (DaN)	940
Structure	Swivel
Version	Axle
Brake	1
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Black painted