Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114A

## **106BISB**

 $\ensuremath{\mathsf{AVO}}$  - Wheel with mechanical cast iron and steel castor for industry, diameter 150mm ean 27922

Material: Mechanical Cast iron Core: Cast Iron Scope: Industry

## Description:

Cast iron wheel, resistant to high temperatures with low rolling resistance. Hub on shielded ball bearings. Special ball bearings for high or low temperatures are available on request.

**Heavy-Duty Castors:** 

Product line: High temperature, Cast Iron



Features Flooring

Minimum temperature: -20 Maximum temperature: 120 Dynamic load capacity: 500 DaN

Rotation: Ball bearing Hardness scale: HB Hardness: 200

AsphaltConcrete

## Wheel data

Diameter (mm)	150
Band width (mm)	38
Hub width (mm)	38
Hub version	Ball bearing
Wheel hole (mm)	17
Bearing seat (mm)	40X12
Dynamic load capacity (DaN)	500
Colour	Grey
Material	Mechanical Cast iron
Box pieces	/
Hardness scale	НВ
Hardness	200

## Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	50
Ground clearance (mm)	184
Castor hole (mm)	/
Static load capacity (DaN)	630
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized