

SERIE 114

105F

AVO - Wheel with mechanical cast iron and steel castor for industry,
diameter 160mm ean 15160

Material: Mechanical Cast
iron

Core: Cast
Iron

Application field:
Industry

Description:

Cast iron wheel, high temperatures resistant with low rolling resistance with pearlitic or laminar structure in accordance with ISO 185. Hub on plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole. Assembled with self-locking nut.

Product line: High temperature, Cast Iron

EAN13:8018793151603

EAN5:15160

Article code:04105F01600GM



Features

Minimum temperature: -40

Maximum temperature: 500

Dynamic load capacity: 300 DaN

Rotation: Plain bore

Hardness scale: HB

Hardness: 200

Flooring

- Asphalt
- Concrete

Wheel data

Diameter (mm)	160
Band width (mm)	40
Hub width (mm)	58
Hub version	Plain bore
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	300
Colour	Grey
Material	Mechanical Cast iron
Box pieces	/
Hardness scale	HB
Hardness	200

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	55
Ground clearance (mm)	194
Castor hole (mm)	16
Static load capacity (DaN)	380
Structure	Swivel
Version	Bolt hole
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized