Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



SERIE 114A

106B

 $\ensuremath{\mathsf{AVO}}$ - Wheel with mechanical cast iron and steel castor for industry, diameter 175mm ean 05517

Material: Mechanical Cast iron Core: Cast Iron Scope: Industry

Description:

Cast iron wheel, resistant to high temperatures with low rolling resistance. Hub on shielded ball bearings. Special ball bearings for high or low temperatures are available on request.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem. Assembled with self-locking nut.

Product line: High temperature, Cast Iron



Features Flooring

Minimum temperature: -20 Maximum temperature: 120 Dynamic load capacity: 800 DaN

Rotation: Ball bearing Hardness scale: HB Hardness: 200

AsphaltConcrete

Wheel data

| Diameter (mm) | 175 |
|-----------------------------|----------------------|
| Band width (mm) | 38 |
| Hub width (mm) | 38 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 20 |
| Bearing seat (mm) | 47X14 |
| Dynamic load capacity (DaN) | 800 |
| Colour | Grey |
| Material | Mechanical Cast iron |
| Box pieces | 1 |
| Hardness scale | НВ |
| Hardness | 200 |

Support data

| Plate size (mm) | 1 |
|----------------------------|---|
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | 1 |
| Offset (mm) | 57 |
| Ground clearance (mm) | 231 |
| Castor hole (mm) | 1 |
| Static load capacity (DaN) | 1000 |
| Structure | Swivel |
| Version | Axle |
| Brake | 1 |
| Plain axle | 25X65 |
| Stem type | Plain axle Stem(on request threaded stem) |
| Finishing | Galvanized |