Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114A

106

 $\ensuremath{\mathsf{AVO}}$  - Wheel with mechanical cast iron and steel castor for industry, diameter 175mm ean 05525

Material: Mechanical Cast iron Core: Cast Iron Scope: Industry

#### Description:

Cast iron wheel, resistant to high temperatures with low rolling resistance. Hub on shielded ball bearings. Special ball bearings for high or low temperatures are available on request.

### **Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate. Assembled with self-locking nut.

Product line: High temperature, Cast Iron



Features Flooring

Minimum temperature: -20 Maximum temperature: 120 Dynamic load capacity: 800 DaN

Rotation: Ball bearing Hardness scale: HB Hardness: 200

# AsphaltConcrete

### Wheel data

Diameter (mm)	175
Band width (mm)	38
Hub width (mm)	38
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	800
Colour	Grey
Material	Mechanical Cast iron
Box pieces	1
Hardness scale	НВ
Hardness	200

## Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	57
Ground clearance (mm)	238
Castor hole (mm)	1
Static load capacity (DaN)	1000
Structure	Swivel
Version	Plate
Brake	1
Plain axle	1
Stem type	1
Finishing	Galvanized