Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114A

## **106BISB**

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 175mm ean 27923

Material: Mechanical Cast

Core: Cast

Application field:

n Industry

Description:

Cast iron wheel, resistant to high temperatures with low rolling resistance. Hub on shielded ball bearings. Special ball bearings for high or low temperatures are available on request.

**Heavy-Duty Castors:** 

Product line: High temperature, Cast Iron

EAN13:8018793279239 EAN5

EAN5:27923

Article code:04106BA1750GP



Features Flooring

Minimum temperature: -20

Maximum temperature: 120

Dynamic load capacity: 800 DaN

AsphaltConcrete

Rotation: Ball bearing

Hardness scale: HB

## Hardness: 200

## Wheel data

Diameter (mm)	175
Band width (mm)	38
Hub width (mm)	38
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	800
Colour	Grey
Material	Mechanical Cast iron
Box pieces	1
Hardness scale	НВ
Hardness	200

## Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	57
Ground clearance (mm)	231
Castor hole (mm)	1
Static load capacity (DaN)	1000
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	25X65
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized