

SERIE 114A

106A

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 200mm ean 05509

Material: Mechanical Cast iron

Core: Cast Iron

Application field: Industry

Description:

Cast iron wheel, resistant to high temperatures with low rolling resistance. Hub on shielded ball bearings. Special ball bearings for high or low temperatures are available on request.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut.

Product line: High temperature, Cast Iron

EAN13:8018793055093

EAN5:05509

Article code:04106A02000GP



Features

Minimum temperature: -20

Maximum temperature: 120

Dynamic load capacity: 800 DaN

- Asphalt
- Concrete

Rotation: Ball bearing

Hardness scale: HB

Hardness: 200

Flooring

Wheel data

Diameter (mm)	200
Band width (mm)	48
Hub width (mm)	48
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	800
Colour	Grey
Material	Mechanical Cast iron
Box pieces	/
Hardness scale	HB
Hardness	200

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	/
Ground clearance (mm)	251
Castor hole (mm)	/
Static load capacity (DaN)	1000
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized