

SERIE 114

108A

AVO - Wheel with mechanical cast iron and steel castor for industry,
diameter 200mm ean 14626

Material: Mechanical Cast iron **Core:** Cast Iron **Scope:** Industry

Description:

Cast iron wheel, high temperatures resistant with low rolling resistance with pearlitic or laminar structure in accordance with ISO 185. Hub on plain bore.

Extra Heavy-Duty Castors:

Made of in pressed and welded high thickness steel, fixed. Black epoxy paint.

Product line: High temperature, Cast Iron

EAN13:8018793146265 **EAN5:**14626 **Article code:**04108A02000GM



Features

Minimum temperature: -40 **Maximum temperature:** 500 **Dynamic load capacity:** 600 DaN
Rotation: Plain bore **Hardness scale:** HB **Hardness:** 200

Flooring

- Asphalt
- Concrete

Wheel data

| | |
|-----------------------------|----------------------|
| Diameter (mm) | 200 |
| Band width (mm) | 50 |
| Hub width (mm) | 58 |
| Hub version | Plain bore |
| Wheel hole (mm) | 20 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 600 |
| Colour | Grey |
| Material | Mechanical Cast iron |
| Box pieces | / |
| Hardness scale | HB |
| Hardness | 200 |

Support data

| | |
|----------------------------|---------------|
| Plate size (mm) | 135X110 |
| Plate hole spacing (mm) | 105X080 |
| Plate hole size (mm) | 13X16 |
| Offset (mm) | / |
| Ground clearance (mm) | 260 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 750 |
| Structure | Fixed |
| Version | / |
| Brake | / |
| Plain axle | / |
| Stem type | / |
| Finishing | Black painted |