Via XX Settembre, 107 28883 Gravellona Toce (VB) - Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114A

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 200mm ean 19517

Material: Mechanical Cast Core: Cast Application field:

Description:

Cast iron wheel, resistant to high temperatures with low rolling resistance. Hub on shielded ball bearings. Special ball bearings for high or low temperatures are available on request.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate and rear brake. Assembled with self-locking nut.

Product line: High temperature, Cast Iron

EAN13:8018793195171 Article code:041060F2000GP EAN5:19517



Flooring Features

Minimum temperature: -20 Dynamic load capacity: 800 DaN Maximum temperature: 120 Asphalt

Rotation: Ball bearing Hardness scale: HB Hardness: 200

Concrete

Wheel data

| Diameter (mm) | 200 |
|-----------------------------|----------------------|
| Band width (mm) | 48 |
| Hub width (mm) | 48 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 25 |
| Bearing seat (mm) | 52X15 |
| Dynamic load capacity (DaN) | 800 |
| Colour | Grey |
| Material | Mechanical Cast iron |
| Box pieces | 1 |
| Hardness scale | НВ |
| Hardness | 200 |

Support data

| Plate size (mm) | 135X110 |
|----------------------------|------------------|
| Plate hole spacing (mm) | 105X080 |
| Plate hole size (mm) | 13X16 |
| Offset (mm) | 57 |
| Ground clearance (mm) | 251 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 1000 |
| Structure | Swivel |
| Version | Plate with brake |
| Brake | Rear |
| Plain axle | 1 |
| Stem type | 1 |
| Finishing | Galvanized |