Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114

## **107BIS**

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 200mm ean 20557

**Material:** Mechanical Cast iron

Core: Cast Iron Application field: Industry

Description:

Cast iron wheel, high temperatures resistant with low rolling resistance with pearlitic or laminar structure in accordance with ISO 185. Hub on plain bore.

## **Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate and rear brake. Assembled with self-locking nut.

Product line: High temperature, Cast Iron

EAN13:8018793205573

EAN5:20557

Article code:041070F2000GM



Features Flooring

Minimum temperature: -40

Maximum temperature: 500

Dynamic load capacity: 600 DaN

AsphaltConcrete

Rotation: Plain bore

Hardness scale: HB

Hardness: 200

## Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	58
Hub version	Plain bore
Wheel hole (mm)	20
Bearing seat (mm)	1
Dynamic load capacity (DaN)	600
Colour	Grey
Material	Mechanical Cast iron
Box pieces	/
Hardness scale	НВ
Hardness	200

## Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	57
Ground clearance (mm)	251
Castor hole (mm)	1
Static load capacity (DaN)	750
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	1
Stem type	I
Finishing	Galvanized