Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114

108BIS

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 200mm ean 20558

Material: Mechanical Cast iron

Core: Cast Iron Application field:

Industry

Description:

Cast iron wheel, high temperatures resistant with low rolling resistance with pearlitic or laminar structure in accordance with ISO 185. Hub on plain bore.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate and rear brake. Black epoxy paint.

Product line: High temperature, Cast Iron

EAN13:8018793205580 **EAN5:**20558

N5:20558 Article code:041080F2000GM



Features Flooring

Minimum temperature: -40

Maximum temperature: 500

Dynamic load capacity: 600 DaN

AsphaltConcrete

Rotation: Plain bore

Hardness scale: HB

Hardness: 200

Taranoo odan ing

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	58
Hub version	Plain bore
Wheel hole (mm)	20
Bearing seat (mm)	1
Dynamic load capacity (DaN)	600
Colour	Grey
Material	Mechanical Cast iron
Box pieces	1
Hardness scale	НВ
Hardness	200

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13
Offset (mm)	57
Ground clearance (mm)	260
Castor hole (mm)	1
Static load capacity (DaN)	750
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	1
Stem type	1
Finishing	Black painted