Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia





SERIE 114

105ANTB

AVO - Wheel made of mechanical cast iron with steel castor for industry, diameter 200mm ean 20609

Material: Mechanical Cast iron Core: Cast Iron Scope: Industry

Description

Cast iron wheel, high temperatures resistant with low rolling resistance with pearlitic or laminar structure in accordance with ISO 185. Hub on plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

Product line: High temperature, Cast Iron



Features Flooring

Minimum temperature: -40 Maximum temperature: 500 Dynamic load capacity: 300 DaN

Rotation: Plain bore Hardness scale: HB Hardness: 200

AsphaltConcrete

Wheel data

5	
Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	58
Hub version	Plain bore
Wheel hole (mm)	20
Bearing seat (mm)	1
Dynamic load capacity (DaN)	300
Colour	Grey
Material	Mechanical Cast iron
Box pieces	1
Hardness scale	НВ
Hardness	200

Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	55
Ground clearance (mm)	232
Castor hole (mm)	1
Static load capacity (DaN)	380
Structure	Swivel
Version	Axle with brake
Brake	Front
Stem	22X50
Stem type	Stem(on request threaded stem)
Finishing	Galvanized