Via XX Settembre, 107 28883 Gravellona Toce (VB) - Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114A

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 200mm ean 27924

Material: Mechanical Cast

Core: Cast

Application field:

Industry

## Description:

Cast iron wheel, resistant to high temperatures with low rolling resistance. Hub on shielded ball bearings. Special ball bearings for high or low temperatures are available on request.

### **Heavy-Duty Castors:**

Product line: High temperature, Cast Iron

EAN13:8018793279246

EAN5:27924

Article code:04106BA2000GP



**Flooring Features** 

Minimum temperature: -20

Maximum temperature: 120

Dynamic load capacity: 800 DaN

 Asphalt Concrete

Rotation: Ball bearing

Hardness scale: HB

Hardness: 200

# Wheel data

Diameter (mm)	200
Band width (mm)	48
Hub width (mm)	48
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	800
Colour	Grey
Material	Mechanical Cast iron
Box pieces	1
Hardness scale	НВ
Hardness	200

# Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	57
Ground clearance (mm)	244
Castor hole (mm)	/
Static load capacity (DaN)	1000
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	25X65
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized