

SERIE 114

## 107BISB

AVO - Wheel made of mechanical cast iron with steel castor for industry, diameter 200mm ean 27926

**Material:** Mechanical Cast iron    **Core:** Cast Iron    **Scope:** Industry

**Description:**

Cast iron wheel, high temperatures resistant with low rolling resistance with pearlitic or laminar structure in accordance with ISO 185. Hub on plain bore.

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

**Product line:** High temperature, Cast Iron

**EAN13:** 8018793279260    **EAN5:** 27926    **Article code:** 04107BF2000GM



## Features

**Minimum temperature:** -40    **Maximum temperature:** 500    **Dynamic load capacity:** 600 DaN  
**Rotation:** Plain bore    **Hardness scale:** HB    **Hardness:** 200

## Flooring

- Asphalt
- Concrete

## Wheel data

|                             |                      |
|-----------------------------|----------------------|
| Diameter (mm)               | 200                  |
| Band width (mm)             | 50                   |
| Hub width (mm)              | 58                   |
| Hub version                 | Plain bore           |
| Wheel hole (mm)             | 20                   |
| Bearing seat (mm)           | /                    |
| Dynamic load capacity (DaN) | 600                  |
| Colour                      | Grey                 |
| Material                    | Mechanical Cast iron |
| Box pieces                  | /                    |
| Hardness scale              | HB                   |
| Hardness                    | 200                  |

## Support data

|                            |                                |
|----------------------------|--------------------------------|
| Plate size (mm)            | /                              |
| Plate hole spacing (mm)    | /                              |
| Plate hole size (mm)       | /                              |
| Offset (mm)                | 57                             |
| Ground clearance (mm)      | 244                            |
| Castor hole (mm)           | /                              |
| Static load capacity (DaN) | 750                            |
| Structure                  | Swivel                         |
| Version                    | Axle with brake                |
| Brake                      | Rear                           |
| Plain axle                 | 25X65                          |
| Stem type                  | Stem(on request threaded stem) |
| Finishing                  | Galvanized                     |