Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



SERIE 114

105B

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 80mm ean 05487

Material: Mechanical Cast iron

Core: Cast Iron

Application field:

Industry

Description:

Cast iron wheel, high temperatures resistant with low rolling resistance with pearlitic or laminar structure in accordance with ISO 185. Hub on plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem. Assembled with self-locking nut.

Product line: High temperature, Cast Iron

EAN13:8018793054874

EAN5:05487

Article code:04105B00800GM



Features Flooring

Minimum temperature: -40

Maximum temperature: 500

Dynamic load capacity: 100 DaN

AsphaltConcrete

Rotation: Plain bore

Hardness scale: HB

Hardness: 200

Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	1
Dynamic load capacity (DaN)	100
Colour	Grey
Material	Mechanical Cast iron
Box pieces	1
Hardness scale	НВ
Hardness	200

Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	37
Ground clearance (mm)	106
Castor hole (mm)	/
Static load capacity (DaN)	130
Structure	Swivel
Version	Axle
Brake	1
Plain axle	20X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized