Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114

108

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 80mm ean 14616

Material: Mechanical Cast iron Core: Cast Iron Scope: Industry

Description:

Cast iron wheel, high temperatures resistant with low rolling resistance with pearlitic or laminar structure in accordance with ISO 185. Hub on plain bore.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate. Black epoxy paint.

Product line: High temperature, Cast Iron



Features Flooring

Minimum temperature: -40 Maximum temperature: 500 Dynamic load capacity: 200 DaN

Rotation: Plain bore Hardness scale: HB Hardness: 200

AsphaltConcrete

Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	1
Dynamic load capacity (DaN)	200
Colour	Grey
Material	Mechanical Cast iron
Box pieces	1
Hardness scale	НВ
Hardness	200

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	11
Offset (mm)	36
Ground clearance (mm)	140
Castor hole (mm)	1
Static load capacity (DaN)	250
Structure	Swivel
Version	Plate
Brake	1
Plain axle	1
Stem type	1
Finishing	Black painted