Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114

105ANTB

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 80mm ean 20603

Material: Mechanical Cast iron Core: Cast Iron Scope: Industry

Description

Cast iron wheel, high temperatures resistant with low rolling resistance with pearlitic or laminar structure in accordance with ISO 185. Hub on plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

Product line: High temperature, Cast Iron

EAN13:8018793206037 **EAN5**:20603 **Article code**:04105BA0800GM



Features Flooring

Minimum temperature: -40 Maximum temperature: 500 Dynamic load capacity: 100 DaN

Rotation: Plain bore Hardness scale: HB Hardness: 200

Asphalt
Caparate

• Concrete

Wheel data

| Diameter (mm) | 80 |
|-----------------------------|----------------------|
| Diameter (mm) | 80 |
| Band width (mm) | 30 |
| Hub width (mm) | 40 |
| Hub version | Plain bore |
| Wheel hole (mm) | 12 |
| Bearing seat (mm) | 1 |
| Dynamic load capacity (DaN) | 100 |
| Colour | Grey |
| Material | Mechanical Cast iron |
| Box pieces | 1 |
| Hardness scale | НВ |
| Hardness | 200 |

Support data

| Plate size (mm) | 1 |
|----------------------------|-----------------|
| Plate hole spacing (mm) | 1 |
| Plate hole size (mm) | 1 |
| Offset (mm) | 37 |
| Ground clearance (mm) | 106 |
| Castor hole (mm) | 1 |
| Static load capacity (DaN) | 130 |
| Structure | Swivel |
| Version | Axle with brake |
| Brake | Front |
| Plain axle | 20X50 |
| Stem type | Plain axle |
| Finishing | Galvanized |