Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 114

107BISB

AVO - Wheel with mechanical cast iron and steel castor for industry, diameter 80mm ean 21504

Material: Mechanical Cast iron Core: Cast Iron Scope: Industry

Description:

Cast iron wheel, high temperatures resistant with low rolling resistance with pearlitic or laminar structure in accordance with ISO 185. Hub on plain bore.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

Product line: High temperature, Cast Iron

EAN13:8018793215046 **EAN5**:21504 **Article code**:04107BF0800GM



Features Flooring

Minimum temperature: -40 Maximum temperature: 500 Dynamic load capacity: 200 DaN

Rotation: Plain bore Hardness scale: HB Hardness: 200

AsphaltConcrete

Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	1
Dynamic load capacity (DaN)	200
Colour	Grey
Material	Mechanical Cast iron
Box pieces	1
Hardness scale	НВ
Hardness	200

Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	36
Ground clearance (mm)	116
Castor hole (mm)	1
Static load capacity (DaN)	250
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized