

SERIE 115

117X

AVO - Wheel with phenolic resin and aisi 304 stainless steel castor for industry, diameter 100mm ean 11366

Material: Phenolic resin

Core: Phenolic resin

Application field: Industry

Description:

Black monolithic high temperature phenolic resin wheels. Hub on plain bore with bushing stainless steel or ball bearing. Stainless steel Teflon bush available on request.

Medium duty castors:

Made of pressed stainless steel AISI 304, turning on double rim of stainless-steel balls AISI 420, with plate.

Product line: High temperature, Stainless steel

EAN13:8018793113663 **EAN5:**11366 **Article code:**06117X01000FN



Features

Minimum temperature: -40

Maximum temperature: 280

Dynamic load capacity: 150 DaN

Rotation: Plain bore

Hardness scale: Shore D

Hardness: 90

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	35
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	150
Colour	Black
Material	Phenolic resin
Box pieces	/
Hardness scale	Shore D
Hardness	90

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	37
Ground clearance (mm)	128
Castor hole (mm)	/
Static load capacity (DaN)	190
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel