

SERIE 115

117BISANTF

AVO - Wheel with phenolic resin and steel castor for industry,
diameter 100mm ean 18427

Material: Phenolic resin

Core: Phenolic resin

Application field: Industry

Description:

Black monolithic high temperature phenolic resin wheels. Hub on plain bore with bushing stainless steel or ball bearing. Stainless steel Teflon bush available on request.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole and front brake. Assembled with self-locking nut.

Product line: High temperature, Stainless steel

EAN13:8018793184274 **EAN5:**18427 **Article code:**05117SFA100FN



Features

Minimum temperature: -40

Maximum temperature: 280

Dynamic load capacity: 150 DaN

Rotation: Plain bore

Hardness scale: Shore D

Hardness: 90

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	35
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	150
Colour	Black
Material	Phenolic resin
Box pieces	/
Hardness scale	Shore D
Hardness	90

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	126
Castor hole (mm)	12
Static load capacity (DaN)	190
Structure	Swivel
Version	Bolt hole with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Galvanized