Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 115

117**BF**

AVO - Wheel with phenolic resin and steel castor for industry, diameter 100mm ean 20890

Material: Phenolic resin Core: Phenolic resin Scope: Industry

Description:

Black monolithic high temperature phenolic resin wheels. Hub on plain bore with bushing stainless steel. Stainless steel Teflon bush available on request.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

Product line: Stainless steel, High temperature

EAN13:8018793208901 **EAN5**:20890 **Article code**:05117BF1000FN



Features Flooring

Minimum temperature: -40 Maximum temperature: 280 Dynamic load capacity: 150 DaN

Hardness scale: Shore D Hardness: 90

Concrete

• Stoneware

Wheel data

Rotation: Plain bore

Diameter (mm)	100
Band width (mm)	35
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	1
Dynamic load capacity (DaN)	150
Colour	Black
Material	Phenolic resin
Box pieces	1
Hardness scale	Shore D
Hardness	90

Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	36
Ground clearance (mm)	131
Castor hole (mm)	/
Static load capacity (DaN)	190
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	22X50
Stem type	Stem(on request threaded stem) Plain axle
Finishing	Galvanized