

SERIE 115

# 117B

AVO - Wheel with phenolic resin and steel castor for industry, diameter 125mm ean 05576

**Material:** Phenolic resin

**Core:** Phenolic resin

**Application field:** Industry

**Description:**

Black monolithic high temperature phenolic resin wheels. Hub on plain bore with bushing stainless steel or ball bearing. Stainless steel Teflon bush available on request.

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem. Assembled with self-locking nut.

**Product line:** High temperature, Stainless steel

**EAN13:**8018793055765 **EAN5:**05576 **Article code:**05117B01250FN



## Features

**Minimum temperature:** -40

**Maximum temperature:** 280

**Dynamic load capacity:** 200 DaN

- Concrete

**Rotation:** Plain bore

**Hardness scale:** Shore D

**Hardness:** 90

- Stoneware

## Flooring

## Wheel data

<b>Diameter (mm)</b>	125
<b>Band width (mm)</b>	40
<b>Hub width (mm)</b>	50
<b>Hub version</b>	Plain bore
<b>Wheel hole (mm)</b>	15
<b>Bearing seat (mm)</b>	/
<b>Dynamic load capacity (DaN)</b>	200
<b>Colour</b>	Black
<b>Material</b>	Phenolic resin
<b>Box pieces</b>	/
<b>Hardness scale</b>	Shore D
<b>Hardness</b>	90

## Support data

<b>Plate size (mm)</b>	/
<b>Plate hole spacing (mm)</b>	/
<b>Plate hole size (mm)</b>	/
<b>Offset (mm)</b>	45
<b>Ground clearance (mm)</b>	161
<b>Castor hole (mm)</b>	/
<b>Static load capacity (DaN)</b>	250
<b>Structure</b>	Swivel
<b>Version</b>	Axle
<b>Brake</b>	/
<b>Plain axle</b>	22X50
<b>Stem type</b>	Plain axle Stem(on request threaded stem)
<b>Finishing</b>	Galvanized