Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 115

117F

 $\ensuremath{\mathsf{AVO}}$ - Wheel with phenolic resin and steel castor for industry, diameter 125mm ean 19590

Material: Phenolic resin

Core: Phenolic resin

Application field:

Industry

Description:

Black monolithic high temperature phenolic resin wheels. Hub on plain bore with bushing stainless steel. Stainless steel Teflon bush available on request.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate and rear brake. Assembled with self-locking nut.

Product line: High temperature, Stainless steel

EAN13:8018793195904

EAN5:19590

Article code:05117F01250FN



Features Flooring

Minimum temperature: -40

Maximum temperature: 280

Dynamic load capacity: 200 DaN

Concrete

Rotation: Plain bore

Hardness scale: Shore D

Hardness: 90

Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	40
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	1
Dynamic load capacity (DaN)	200
Colour	Black
Material	Phenolic resin
Box pieces	1
Hardness scale	Shore D
Hardness	90

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	45
Ground clearance (mm)	166
Castor hole (mm)	1
Static load capacity (DaN)	250
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	1
Stem type	1
Finishing	Galvanized