

SERIE 115

# 117BISANTF

AVO - Wheel with phenolic resin and steel castor for industry, diameter 125mm ean 19634

**Material:** Phenolic resin

**Core:** Phenolic resin

**Application field:** Industry

**Description:**

Black monolithic high temperature phenolic resin wheels. Hub on plain bore with bushing stainless steel or ball bearing. Stainless steel Teflon bush available on request.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole and front brake. Assembled with self-locking nut.

**Product line:** High temperature, Stainless steel

**EAN13:**8018793196345 **EAN5:**19634 **Article code:**05117SFA125FN



## Features

**Minimum temperature:** -40

**Maximum temperature:** 280

**Dynamic load capacity:** 170 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore D

**Hardness:** 90

## Flooring

- Concrete
- Stoneware

## Wheel data

Diameter (mm)	125
Band width (mm)	40
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	170
Colour	Black
Material	Phenolic resin
Box pieces	/
Hardness scale	Shore D
Hardness	90

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	42
Ground clearance (mm)	150
Castor hole (mm)	12
Static load capacity (DaN)	220
Structure	Swivel
Version	Bolt hole with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Galvanized