

SERIE 115

# 117F

**AVO - Wheel with phenolic resin and steel castor for industry, diameter 160mm ean 21706**

**Material:** Phenolic resin

**Core:** Phenolic resin

**Application field:** Industry

**Description:**

Black monolithic high temperature phenolic resin wheels. Hub on plain bore with bushing stainless steel or ball bearing. Stainless steel Teflon bush available on request.

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate and rear brake. Assembled with self-locking nut.

**Product line:** High temperature, Stainless steel

**EAN13:**8018793217064 **EAN5:**21706 **Article code:**05117F01600FN



## Features

**Minimum temperature:** -40

**Maximum temperature:** 280

**Dynamic load capacity:** 250 DaN

- Concrete

**Rotation:** Plain bore

**Hardness scale:** Shore D

**Hardness:** 90

- Stoneware

## Flooring

## Wheel data

Diameter (mm)	160
Band width (mm)	50
Hub width (mm)	58
Hub version	Plain bore
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	250
Colour	Black
Material	Phenolic resin
Box pieces	/
Hardness scale	Shore D
Hardness	90

## Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	45
Ground clearance (mm)	207
Castor hole (mm)	/
Static load capacity (DaN)	320
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	/
Stem type	/
Finishing	Galvanized