Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 115

117B

AVO - Wheel with phenolic resin and steel castor for industry, diameter 80mm ean 05574

Material: Phenolic resin

Core: Phenolic resin

Application field:

Industry

Description:

Black monolithic high temperature phenolic resin wheels. Hub on plain bore with bushing stainless steel. Stainless steel Teflon bush available on request.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem. Assembled with self-locking nut.

Product line: High temperature, Stainless steel

EAN13:8018793055741

EAN5:05574

Article code:05117B00800FN



Features Flooring

Minimum temperature: -40

Maximum temperature: 280

Dynamic load capacity: 100 DaN

ConcreteStoneware

Rotation: Plain bore

Hardness scale: Shore D

Hardness: 90

Wheel data

Diameter (mm)	80
Band width (mm)	35
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	1
Dynamic load capacity (DaN)	100
Colour	Black
Material	Phenolic resin
Box pieces	/
Hardness scale	Shore D
Hardness	90

Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	36
Ground clearance (mm)	114
Castor hole (mm)	/
Static load capacity (DaN)	130
Structure	Swivel
Version	Axle
Brake	1
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized