Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

**SERIE 115** 

# 117BISANT

AVO - Wheel with phenolic resin and steel castor for industry, diameter 80mm ean 18637

Material: Phenolic resin

Core: Phenolic resin

Application field:

Industry

#### Description:

Black monolithic high temperature phenolic resin wheels. Hub on plain bore with bushing stainless steel. Stainless steel Teflon bush available on request.

#### Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls

Product line: High temperature, Stainless steel

EAN13:8018793186377

EAN5:18637

Article code:05117S0A080FN



Features Flooring

Minimum temperature: -40

Maximum temperature: 280

Dynamic load capacity: 100 DaN

• Concrete

Rotation: Plain bore Hardness scale: Shore D

Hardness: 90

Stoneware

### Wheel data

Diameter (mm)	80
Diameter (IIIII)	00
Band width (mm)	35
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	1
Dynamic load capacity (DaN)	100
Colour	Black
Material	Phenolic resin
Box pieces	1
Hardness scale	Shore D
Hardness	90

## Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	37
Ground clearance (mm)	108
Castor hole (mm)	1
Static load capacity (DaN)	130
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	1
Stem type	1
Finishing	Galvanized