

SERIE 115

117BISANT

AVO - Wheel with phenolic resin and steel castor for industry, diameter 80mm ean 18637

Material: Phenolic resin

Core: Phenolic resin

Application field: Industry

Description:

Black monolithic high temperature phenolic resin wheels. Hub on plain bore with bushing stainless steel or ball bearing. Stainless steel Teflon bush available on request.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls.

Product line: High temperature, Stainless steel

EAN13:8018793186377 **EAN5:**18637 **Article code:**05117S0A080FN



Features

Minimum temperature: -40

Maximum temperature: 280

Dynamic load capacity: 100 DaN

Rotation: Plain bore

Hardness scale: Shore D

Hardness: 90

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	80
Band width (mm)	35
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	100
Colour	Black
Material	Phenolic resin
Box pieces	/
Hardness scale	Shore D
Hardness	90

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	37
Ground clearance (mm)	108
Castor hole (mm)	/
Static load capacity (DaN)	130
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Galvanized