

SERIE 116C

# 116C

AVO - Wheel with 30% glass-filled polyamide 6 for industry,  
diameter 60mm ean 22020

**Material:** 30% glass-filled  
Polyamide 6

**Core:** Glass-filled  
polyamide 6

**Application field:**  
Industry

**Description:**

Polyamide 6 wheel with 30% fiber glass. Hub on plain bore.

**Product line:** High temperature, Stainless steel, Polyamide

**EAN13:**8018793220200 **EAN5:**22020 **Article code:**G511600060CFP



## Features

**Minimum temperature:** -25

**Maximum temperature:** 120

**Dynamic load capacity:** 150 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore D

**Hardness:** 80

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

Diameter (mm)	60
Band width (mm)	35
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	150
Colour	Grey
Material	30% glass-filled Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	80

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/