

SERIE 116C

98XANT

AVO - Wheel with 30% glass-filled polyamide 6 and aisi 304 stainless steel castor for industry, diameter 100mm ean 22176

Material: 30% glass-filled Polyamide 6

Core: Glass-filled polyamide 6

Application field: Industry

Description:

Polyamide 6 wheel with 30% fiber glass. Hub on plain bore.

Medium duty castors:

Made of pressed steel AISI 304, turning on double rim of stainless-steel balls AISI 420, with plate and front brake. Dust cover ring on the balls.

Product line: Stainless steel, Polyamide, High temperature

EAN13:8018793221764 **EAN5:**22176 **Article code:**05X980A1000FN



Features

Minimum temperature: -25

Maximum temperature: 120

Dynamic load capacity: 120 DaN

Rotation: Plain bore

Hardness scale: Shore D

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

| | |
|-----------------------------|------------------------------|
| Diameter (mm) | 100 |
| Band width (mm) | 30 |
| Hub width (mm) | 40 |
| Hub version | Plain bore |
| Wheel hole (mm) | 12 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 120 |
| Colour | Grey |
| Material | 30% glass-filled Polyamide 6 |
| Box pieces | / |
| Hardness scale | Shore D |
| Hardness | 80 |

Support data

| | |
|----------------------------|--------------------------|
| Plate size (mm) | 100X085 |
| Plate hole spacing (mm) | 080X060 |
| Plate hole size (mm) | 8,5X12 |
| Offset (mm) | 37 |
| Ground clearance (mm) | 128 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 150 |
| Structure | Swivel |
| Version | Plate with brake |
| Brake | Front |
| Plain axle | / |
| Stem type | / |
| Finishing | AISI 304 stainless steel |