

SERIE 116C

98XF

AVO - Wheel with 30% glass-filled polyamide 6 and aisi 304 stainless steel castor for industry, diameter 125mm ean 28018

Material: 30% glass-filled Polyamide 6

Core: Glass-filled polyamide 6

Application field: Industry

Description:

Polyamide 6 wheel with 30% fiber glass. Hub on plain bore.

Medium duty castors:

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with bolt hole. Dust cover ring on the balls.

Product line: Stainless steel, High temperature, Polyamide

EAN13:8018793280181

EAN5:28018

Article code:05X98F01250FN



Features

Minimum temperature: -25

Maximum temperature: 120

Dynamic load capacity: 170 DaN

Rotation: Plain bore

Hardness scale: Shore D

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	40
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	170
Colour	Grey
Material	30% glass-filled Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	80

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	42
Ground clearance (mm)	150
Castor hole (mm)	12
Static load capacity (DaN)	220
Structure	Swivel
Version	Bolt hole
Brake	/
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel