

SERIE 116C

98X

AVO - Wheel with 30% glass-filled polyamide 6 and aisi 304 stainless steel castor for industry, diameter 200mm ean 26837

Material: 30% glass-filled Polyamide 6

Core: Glass-filled polyamide 6

Application field: Industry

Description:

Polyamide 6 wheel with 30% fiber glass. Hub on plain bore.

Medium duty castors:

En acier inoxydable embouti AISI 304, pivotant sur double rangée de billes en inox AISI 420, avec platine.

Product line: Stainless steel, High temperature, Polyamide

EAN13:8018793268370

EAN5:26837

Article code:05X98002000FN



Features

Minimum temperature: -25

Maximum temperature: 120

Dynamic load capacity: 300 DaN

Rotation: Plain bore

Hardness scale: Shore D

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	58
Hub version	Plain bore
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	300
Colour	Grey
Material	30% glass-filled Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	80

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	55
Ground clearance (mm)	235
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel