

SERIE 116C

## 98XF

**AVO - Wheel with 30% glass-filled polyamide 6 and aisi 304 stainless steel castor for industry, diameter 80mm ean 28017**

**Material:** 30% glass-filled Polyamide 6

**Core:** Glass-filled polyamide 6

**Application field:** Industry

**Description:**

Polyamide 6 wheel with 30% fiber glass. Hub on plain bore.

**Medium duty castors:**

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with bolt hole. Dust cover ring on the balls.

**Product line:** Stainless steel, High temperature, Polyamide

**EAN13:**8018793280174    **EAN5:**28017    **Article code:**05X98F00800FN



## Features

**Minimum temperature:** -25

**Maximum temperature:** 120

**Dynamic load capacity:** 120 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore D

**Hardness:** 80

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

<b>Diameter (mm)</b>	80
<b>Band width (mm)</b>	30
<b>Hub width (mm)</b>	40
<b>Hub version</b>	Plain bore
<b>Wheel hole (mm)</b>	12
<b>Bearing seat (mm)</b>	/
<b>Dynamic load capacity (DaN)</b>	120
<b>Colour</b>	Grey
<b>Material</b>	30% glass-filled Polyamide 6
<b>Box pieces</b>	/
<b>Hardness scale</b>	Shore D
<b>Hardness</b>	80

## Support data

<b>Plate size (mm)</b>	/
<b>Plate hole spacing (mm)</b>	/
<b>Plate hole size (mm)</b>	/
<b>Offset (mm)</b>	37
<b>Ground clearance (mm)</b>	106
<b>Castor hole (mm)</b>	12
<b>Static load capacity (DaN)</b>	150
<b>Structure</b>	Swivel
<b>Version</b>	Bolt hole
<b>Brake</b>	/
<b>Plain axle</b>	/
<b>Stem type</b>	/
<b>Finishing</b>	AISI 304 stainless steel